





info@atkequipment.co.uk www.atkequipment.co.uk





## 2.5YD STATIC COMPACTOR FOR HAND LOADING

Motor Rating	7.5	KW
Power Supply Rating	415	VOLT 3 PHASE 32 AMP
Control Panel Voltage	24	VOLT
Clear Aperture Width	1430	MM
Clear Aperture Length	1400	MM
Charge Box Depth	940	MM
Charge Box Volume	1.88	$M^3$
CHEM Volume Per Stroke	1.60	$M^3$
Cycle Time	45	SEC
CHEM Volume Per Hour	1.51	$M^3$
Overall Height (Top of Flange)	1300	MM
Overall Length	4020	MM
Overall Width	1720	MM
Basic Hydraulic Pressure	150	BAR
Hydraulic Capacity	150	LITRES
Total Weight	2.8	TONNE



0845 603 6764



info@atkequipment.co.uk www.atkequipment.co.uk





## 2.5YD STATIC COMPACTOR WITH BIN LIFTER

Motor Rating	7.5	KW
Power Supply Rating	415	VOLT 3 PHASE 32 AMP
Control Panel Voltage	24	VOLT
Clear Aperture Width	1430	MM
Clear Aperture Length	1400	MM
Charge Box Depth	940	MM
Charge Box Volume	1.88	$M^3$
CHEM Volume Per Stroke	1.60	$M^3$
Cycle Time	54	SEC
CHEM Volume Per Hour	1.51	$M^3$
Overall Height (Excluding Hopper)	1300	MM
Overall Length	4020	MM
Overall Width (Excluding Cage)	2220	MM
Basic Hydraulic Pressure	150	BAR
Hydraulic Capacity	150	LITRES
Total Weight	3.4	TONNE

If the machine is fitted with a Side Loading Bin Lifter with standard End Entry Cage the overall width would be 4720mm.



0845 603 6764



info@atkequipment.co.uk www.atkequipment.co.uk





## **4YD STATIC COMPACTOR FOR HAND LOADING**

Motor Rating	11	<b>(W</b>
Power Supply Rating	415 \	OLT 3 PHASE 45 AMP
Control Panel Voltage	24 \	/OLT
Clear Aperture Width	1500	MM
Clear Aperture Length	2200 1	MM
Charge Box Depth	940 1	MM
Press Force	38 1	ΓONNE
Cycle Time	60 9	SEC
Cylinder Bore	160 1	MM
Overall Height (Top of Flange)	1300	MM (not including hopper)
Overall Length	5175 N	MM
Overall Width	1880	MM
Basic Hydraulic Pressure	150 E	BAR
Ram Penetration	400 1	MM
Hydraulic Capacity	250 l	LITRES
Total Weight	3.9 1	TONNE